SPECIFICATIONS

RAISING YOUR EXPECTATIONS WAS ALWAYS OURS.

www.skidsteer.com

240 Series II Skid Steer

- Patented vertical-lift system provides greater reach than conventional skid steers, for precise center load placement and quick, efficient truck loading.
- 53-hp John Deere 3029D high-torque engine with direct injection has exclusive wet-sleeve design, high-ring pistons, and precision joint-connecting rods. This easy-starting, durable engine is extremely fuel efficient.
- Quick-lift cab, removable side panels, and easy-access top and rear doors permit convenient maintenance and service.
- Superior 360-degree visibility results in greater productivity and safe operation. Unique boom arm design provides maximum bucket visibility.
- Available cab enclosure, air conditioner, and heater/defroster provide year-round climate control.
- Optional hydraulic Quik-Tatch™ latches/unlatches at the touch of a switch for convenient in-the-seat attachment switchover.
- Strong machine forces include — 5,500 lb. bucket breakout, 6,165-lb. operating weight, 4,450-ft.-lb. axle torque, and 3,400-lb. tipping load. Rated Operating Capacity (R.O.C.) is 1,500 lb. (2,000 lb. with optional counterweight).
- 114-in. hinge pin height easily clears 9-ft. truck sideboards for fast, efficient truck loading.
- Steep 45-degree dump angle and high 35-degree bucket rollback make for more efficient load carrying and quicker cycle times.

240 Series II	
Engine	John Deere
Model	3029D
Displacement	179 cu. in. (2.9 L)
Cylinders	3
Horsepower	53 hp (39.5 kW) gross / 51 hp (38 kW) net
Rated Engine Speed	2,400 rpm
Fuel Capacity	15 U.S. gal. (57 L)
Performance:	
SAE Rated Operating Capacity	1,500 lb. (681 kg)
With Optional Counterweights	2,000 lb. (907 kg)
Tipping Load	3,400 lb. (1542 kg)
Breakout Force:	
Foundry Bucket	5,500 lb. (2495 kg)
Construction Bucket	3,900 lb. (1769 kg)
Ground Speed:	
Single Speed	6.7 mph (10.8 km/h)
Maximum Axle Torque	4,450 ft.-lb. (6033 Nm)
Operating Weight	6,165 lb. (2796 kg)
Hydraulics:	
Hydraulic Pressure	3,100 psi
Hydraulic Pump:	
Standard Flow	14.6 gpm (55.3 L/min.)
High Flow	25.4 gpm (96.1 L/min.)
Hydraulic Horsepower:	
Standard Flow	26.4 hp (19.7 kW)
High Flow	45.9 hp (34.2 kW)
Transmission	Hydrostatic four-wheel drive
Dimensions:	
Length without Bucket	102 in. (2591 mm)
Length with Bucket	125.8 in. (3196 mm)
Width without Bucket	63.7 in. (1618 mm)
Height to ROPS	75.4 in. (1915 mm)
Height to Hinge Pin	114 in. (2895 mm)
Dump Reach:	
Heavy-Duty Foundry Bucket	29.1 in. (738 mm)
Heavy-Duty Construction Bucket	36.1 in. (917 mm)
Dump Angle (At Full Height)	45 degrees
Bucket Rollback (At Ground)	35 degrees
Wheelbase	42.3 in. (1075 mm)
Ground Clearance	8.2 in. (209 mm)
Angle of Departure	27 degrees
Standard Tire Size	10x16.5 SKS, Extra-Wall, 8-ply rating
John Deere Standard Warranty	1-year unlimited hours

Standard Equipment

Adjustable Armrests, Patent Pending
Adjustable Foot Pedals
Air Heat Cold Start
Auxiliary Hydraulics
Convenient Front and Rear Tie Downs
Deluxe Seat
Four Grab Handles
Front and Rear Work Lights
Integral Cab Boom Locks
John Deere Manufactured Hydraulic Cylinders
John Deere PowerTech® Engine
Meters/Gauges/Warning Lights
Patented John Deere Quik-Tatch
Patented Vertical-Lift Boom
Quick-Pivot ROPS
Rear Window
Seat Belt with Auto Recoil
Triple-Interlock Control System
Wet Disk Brakes
8 pr. 10x16.5 SKS Extra-Wall Tires
55-Amp Alternator

Options/Accessories

Air Conditioning with Heater/Defroster
Auto Preheat
Auto Shutdown with Alarm
Backup Alarm
Block Heater Kit
Cab Enclosure
Demolition Door Kit
Dual Flashers Kit
Floor Cover Plates
Hand Controls
Heater/Defroster Kit
High-Flow Hydraulics
Horn
Hydraulic Quik-Tatch
Hydraulic Self-Leveling Kit
Quik-Tatch Weights
Rear Weight Brackets
Rearview Mirror Kit
Shoulder Belt
Side Window Kit
SMV Sign
Suspension Seat
Top Window
Vinyl Cab Enclosure
Warning Beacon
3-Inch Seat Belt
8-Button Handle
12-Volt Receptacle Kit

John Deere Worksite Pro™ Attachments

Ag Utility Grapple
Angle Brooms
Augers
Backhoes
Bale Spear
Cold Planers
Construction, Foundry, Manure/Slurry, and Utility Buckets
Hydraulic Breakers
Multi-Purpose Buckets
Pallet Forks
Pick-Up Brooms
Power Rakes
Rotary Tillers
Scrap Grapples
Snow/Utility Blades
Three-Point Hitch
Tined/Brush Grapples
Tooth Bars
Tracks
Trenchers
Vibratory Rollers

Due to various widths, not all attachment sizes offered are compatible with all 200 Series Skid Steers.

(Dimensions and specifications in accordance with SAE and ISO standards. Rated Operating Capacity with 66-in. Foundry Bucket and standard tires per SAE Standard J818.)

SAFETY live with it

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

JOHN DEERE

DKA240IICWP Litho in U.S.A. (03-02)

NOTHING RUNS LIKE A DEERE®