SPECIFICATIONS

360-DEGREE VISIBILITY IS YOUR WINDOW OF OPPORTUNITY.

www.skidsteer.com

260 Series II Skid Steer

- Patented vertical-lift system with cushioned boom cylinders provides greater reach than conventional skid steers, for precise center load placement and quick, efficient truck loading.
- 72-hp John Deere 3029T high-torque, turbocharged engine with direct injection has exclusive wet-sleeve design, high-ring pistons, and precision joint-connecting rods. This easy-starting, durable engine is extremely fuel efficient.
- Optional two-speed (up to 12 mph) transmission is available for increased productivity.
- Quick-lift cab, removable side panels, and easy-access top and rear doors permit convenient maintenance and service.
- Superior 360-degree visibility results in greater productivity and safe operation. Unique boom arm design provides maximum bucket visibility.
- Steep 45-degree dump angle and high 35-degree bucket rollback make for more efficient load carrying and quicker cycle times.
- Available cab enclosure, air conditioner, and heater/defroster provide year-round climate control.
- Optional hydraulic Quik-Tatch™ latches/unlatches at the touch of a switch for convenient in-the-seat attachment switchover.
- Strong machine forces include — 7,500-lb. bucket breakout, 4,800-lb. boom breakout, 5,750-ft.-lb. axle torque, and 5,000-lb. tipping load. Rated Operating Capacity (R.O.C.) is 2,400 lb. (2,600 lb. with optional counterweight).
- 127-in. hinge pin height easily clears 10-ft. truck sideboards for fast, efficient truck loading.

260 Series II

Engine	John Deere
Model	3029T
Displacement	179 cu. in. (2.9 L)
Cylinders	3
Horsepower	72.4 hp (54 kW) gross / 69 hp (51.5 kW) net
Rated Engine Speed	2,400 rpm
Fuel Capacity	20 U.S. gal. (76 L)
Performance:	
SAE Rated Operating Capacity	2,400 lb. (1089 kg)
With Optional Counterweights	2,600 lb. (1180 kg)
Tipping Load	5,000 lb. (2268 kg)
Breakout Force:	
Heavy-Duty Foundry Bucket	7,500 lb. (3402 kg)
Heavy-Duty Construction Bucket	5,300 lb. (2404 kg)
Ground Speed:	
Single Speed	7.0 mph (11.3 km/h)
Two-Speed, Low	7.0 mph (11.3 km/h)
Two-Speed, High	12.0 mph (19.3 km/h)
Maximum Axle Torque	5,750 ft.-lb. (7796 Nm)
Operating Weight	8,250 lb. (3742 kg)
Hydraulics:	
Hydraulic Pressure	3,100 psi
Hydraulic Pump:	
Standard Flow	21.3 gpm (80.6 L/min.)
High Flow	33.1 gpm (125.3 L/min.)
Hydraulic Horsepower:	
Standard Flow	38.5 hp (28.7 kW)
High Flow	59.9 hp (44.7 kW)
Transmission	Hydrostatic four-wheel drive
Dimensions:	
Length without Bucket	115 in. (2921 mm)
Length with Bucket	138 in. (3504 mm)
Width without Bucket	76.2 in. (1935 mm)
Height to ROPS	82.9 in. (2105 mm)
Height to Hinge Pin	127 in. (3226 mm)
Dump Reach :	
Heavy-Duty Foundry Bucket	32 in. (813 mm)
Heavy-Duty Construction Bucket	39 in. (991 mm)
Dump Angle (At Full Height)	45 degrees
Bucket Rollback (At Ground)	35 degrees
Wheelbase	47.6 in. (1209 mm)
Ground Clearance	11 in. (280 mm)
Angle of Departure	27 degrees
Standard Tire Size	14x17.5 SKS Extra-Wall, 12-ply rating
John Deere Standard Warranty	1-year unlimited hours

(Dimensions and specifications in accordance with SAE and ISO standards. Rated Operating Capacity with 78-in. Heavy-Duty Foundry Bucket and standard tires per SAE Standard J818.)

Standard Equipment

- Adjustable Armrests, Patent Pending
- Adjustable Foot Pedals
- Air Heat Cold Start
- Auxiliary Hydraulics
- Convenient Front and Rear Tie Downs
- Deluxe Seat
- Four Grab Handles
- Front and Rear Work Lights
- Integral Cab Boom Locks
- John Deere Manufactured Hydraulic Cylinders
- Meters/Gauges/Warning Lights
- Patented John Deere Quik-Tatch
- Patented Vertical-Lift Boom
- Quick-Pivot ROPS
- Rear Window
- Seat Belt with Auto Recoil
- Triple Interlock Control System
- Turbocharged John Deere PowerTech® Engine
- Wet Disk Brakes
- 12 pr. 14x17.5 SKS Extra-Wall Tires
- 55-Amp Alternator

Options/Accessories

- Air Conditioning with Heater/Defroster
- Auto Preheat
- Auto Shutdown with Alarm
- Backup Alarm
- Block Heater Kit
- Cab Enclosure
- Demolition Door Kit
- Dual Flashers Kit
- Floor Cover Plates
- Hand Controls
- Heater/Defroster Kit
- High-Flow Hydraulics
- Horn
- Hydraulic Quik-Tatch
- Hydraulic Self-Leveling Kit
- Quik-Tatch Weights
- Rear Weight Brackets
- Rearview Mirror Kit
- Shoulder Belt
- Side Window Kit
- SMV Sign
- Suspension Seat
- Top Window
- Vinyl Cab Enclosure
- Warning Beacon
- 2-Speed Transmission
- 3-Inch Seat Belt
- 8-Button Handle
- 12-Volt Receptacle Kit

John Deere Worksite Pro™ Attachments

- Ag Utility Grapple
- Angle Brooms
- Augers
- Backhoes
- Bale Spear
- Cold Planers
- Construction, Foundry, Manure/Slurry, and Utility Buckets
- Hydraulic Breakers
- Multi-Purpose Buckets
- Pallet Forks
- Pick-Up Brooms
- Power Rakes
- Rotary Tillers
- Scrap Grapples
- Snow/Utility Blades
- Three-Point Hitch
- Tined/Brush Grapples
- Tooth Bars
- Tracks
- Trenchers
- Vibratory Rollers

Due to various widths, not all attachment sizes offered are compatible with all 200 Series Skid Steers.

SAFETY live with it

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

JOHN DEERE

DKA260IICWP Litho in U.S.A. (03-02)

NOTHING RUNS LIKE A DEERE®