



POWER CUTTERS

HUSQVARNA K 7000 RING

Art.no: 970 75 63 01

Husqvarna K 7000 Ring is equipped with high frequency PRIME™ technology, making it our most powerful electric cutter ever. The high power output, well-balanced body and low vibration levels make this machine very efficient and easy to use. The PRIME™ product range enables you to combine the system that is most efficient for your business. K 7000 Ring can be used either with PP 70, PP 220 or PP 492 as a power source. Expand the system as your needs develop.

FEATURES



X-Halt™ – blade brake operation with PRIME™

Connecting your PRIME™ product to a PP 8 or PP 70 gives you access to the X-Halt™ blade brake function, capable of stopping the rotation of the blade in a fraction of a second.



Explore the modular power of PRIME™

PRIME™ stands for Powerful, Revolutionary, Intelligent, Modular and Electric. Which means great cutting, sawing and drilling power in a compact, sturdy and flexible package. If you need high-performance electric equipment that can handle most jobs, PRIME™ is for you.



Deep cutting

Thanks to the peripheral drive you can cut far deeper than with a traditional power cutter. The cutting depth of 325 mm is sufficient to cut through a normal wall from one side only.

Higher productivity

This machine is controlled by a power pack with built-in intelligence that communicates with the machine motor to ensure optimal power and rpm for each cutting job.

TECHNICAL DATA HUSQVARNA K 7000 RING

Art.no: 970 75 63 01

HUSQVARNA K 7000 RING

ENGINE

Output power	7.4 hp
Power Source	Corded

MOTOR

Rated input power	4/ 7.4 hp
Frequency	50/60 Hz
Phases	1 and 3 ph

CUTTING EQUIPMENT

Cutting depth, max	10.6 in
Blade diameter, max	14 in
Blade thickness, max	0.2 in
Peripheral speed, max	10,800 fpm
Coolant	Wet

DIMENSIONS

Product size length	28.8 in
Product size width	8.6 in
Product size height	17 in
Weight	26.5 lbs
Packaging length (Calc)	34.646 in
Packaging width (Calc)	11.811 in
Packaging height (Calc)	19.291 in
Article gross weight (Calc)	59.856 lbs

SOUND AND NOISE

Sound power level, guaranteed (LWA)	111 dB(A)
Sound pressure level at operators ear (LpA)	102 dB(A)

VIBRATION

Vibrations left/front handle	2.4 m/s ²
Vibrations right/rear handle	1.5 m/s ²



View all product details on:

<https://www.husqvarnaconstruction.com/us/power-cutters/k7000-ring/>