POWER CUTTERS

HUSQVARNA K 760 CUT-N-BREAK II

Art.no: 967 19 57 01

Our Cut-n-Break method is the natural choice when you need to cut deep without overcutting at the corners. The K 760 Cut-n-Break enables you to cut as deep as 16" from one side. The two high-speed blades make a core in the saw cut, which can then easily be broken off using the accompanying breaking tool. This way you easily work your way through the material, at a very low diamond tool and maintenance cost. Delivered with twin blades and a breaking tool.

FEATURES

Cost-efficient cutting method

With the unique cut-n-break method you can work your way through the material step-by step at a low tool cost.

Exceptional cutting depth

The long body and double cutting blades allow you to make cuts up to 16" deep.

High performing blades included

Twin blades, with a very stable core and cutting performance are delivered with the machine.

Optimized engine performance

Optimized engine performance through efficient cylinder design, digital ignition system and X-Torq® engine technology.

TECHNICAL DATA HUSQVARNA K 760 CUT-N-BREAK II

Art.no: 967 19 57 01

HUSQVARNA K 760 CUT-N-BREAK II

ENGINE

Output power	5 hp
Max engine/motor	9,300 rpm
Maximum power speed	9,000 rpm
Cylinders	1
Number of strokes	2-stroke engine
Exhaust emissions (CO, EU V)	711 g/kWh
Power Source	Petrol

CUTTING EQUIPMENT

Cutting depth, max	16 in
Blade diameter, max	9 in
Peripheral speed, max	16,000 fpm
Coolant	Wet

DIMENSIONS

Product size length	31.42 in
Product size width	9.69 in
Product size height	17.56 in
Weight	21.2 lbs
Packaging length (Calc)	35.039 in
Packaging width (Calc)	10.63 in
Packaging height (Calc)	16.535 in
Article gross weight (Calc)	31.658 lbs

SOUND AND NOISE

Sound power level, guaranteed (LWA)	115 dB(A)
Sound pressure level at operators ear (LpA)	101 dB(A)

VIBRATION

Vibrations left/front handle	1.9 m/s²
Vibrations right/rear handle	2.8 m/s²

View all product details on:

https://www.husqvarnaconstruction.com/us/power-cutters/k760-cut-n-break-ii/